In-Wall Home Theater Power Management

MIW-POWER-PRO-PFP

Provides Safe and Noise Filtered Power to remote Plasma Screens, LCD's and Ceiling Projectors

wo recessed AC receptacles deliver power to remotely located devices. Enlarged faceplate (4.5" x 4.5") accommodates oversized wall cutouts. Line fault LED to indicate an overvoltage condition with the power to the MIW-POWER -PRO-PFP. Power ON LED indicates power is being supplied to the MIW-POWER-PRO-PFP outlets.

Voltage monitoring Circuit protects equipment against prolonged over voltages by disconnecting the power and reconnecting it when safe power returns.

May be used in conjunction with MIW-DUAL-SIGNAL BAY PFP and signal line modules (sold separately).

3 Year Product Warranty and Limited Lifetime Connected Equipment Protection Policy when properly installed using MIW-DUAL-SIGNAL BAY PFP and appropriate MIW Module (both sold separately).



MIW-DUAL SIGNAL BAY-PFP (sold separately). (modules sold separately)

Contact PFP for information.

INSTALLED BEHIND DISPLAY MONITOR

Power to Remotely Located Devices



| AC CIRCUIT | |
|--|--|
| AC Outlets, Total Line Voltage Total Current Capacity UL 1449 Suppresion Rating Protection Modes Energy Dissipation Peak Impulse Current Catastrophic Surge Circuit Thermal Fusing | 120V, 60Hz 15A 330V L-N, L-G, N-G 546 Joules 32,500 Amps Yes |

| VOLIAGE MONITORI | |
|-----------------------------|------------------|
| Over-voltage Shutoff | 142 VAC ± 5 VAC |
| Design and specifications s | |
| notice due to produ | uct improvement. |

| POWER OUTLET FACEPLATE | |
|--|--|
| Over-voltage Shutoff | |
| SHIPPING DIMENSIONS, WEIGHTS & UPC CODES | |
| Single Pack Dimensions 4.5"W x 2"D x 4.5'H Single Pack Weight 2 lbs. Single Unit UPC 0 50616 00840 2 | |
| Master Pack Dimensions 11"W x 7"D x 11'H Master Pack Quantity | |

MODEL: MIW-POWER-PRO-PFP

